

04/08/99  
jc553 U.S. PTO

ASSISTANT COMMISSIONER FOR PATENTS  
Washington, D.C. 20231

PATENT

Date: April 8, 1999  
File No.: 1201.62820

Sir:

Transmitted herewith for filing is the patent application of

Inventor(s): David J. Beebe, Ian K. Glasgow,  
Matthew B. Wheeler

For: MICROFLUIDIC EMBRYO AND/OR  
OOCTE HANDLING DEVICE  
AND METHOD

I hereby certify that this paper is being deposited with  
the United States Postal Service as Express Mail in an  
envelope addressed to: BOX PATENT APPLICATION,  
ASSISTANT COMMISSIONER FOR PATENTS,  
Washington, D.C. 20231, on this date.

04/08/99

Date

Express Mail No. EM045518299US

Enclosed are:

- (X) 23 pages of specification, including 22 claims and an abstract.
- ( ) an executed oath or declaration, with power of attorney.
- (X) an unexecuted oath or declaration, with power of attorney.
- (X) 4 sheet(s) of informal drawing(s).
- ( ) sheet(s) of formal drawings(s).
- ( ) Assignment(s) of the invention to \_\_\_\_\_
- ( ) Assignment Form Cover Sheet.
- ( ) A check in the amount of \$\_\_\_\_\_ to cover the fee for recording the assignment(s)  
is enclosed.
- ( ) Information Disclosure Statement.
- ( ) Form PTO-1449 and cited references.
- ( ) Associate Power of Attorney.
- ( ) Priority Document.
- ( ) Associate power of attorney.

jc518 U.S. PTO  
09/289137  
04/08/99

Fee Calculation For Claims As Filed

a) Basic Fee						\$ 760.00
b) Independent Claims	<u>3</u>	-	3	=	<u>0</u>	x \$ 78.00 = \$ <u>0</u>
c) Total Claims	<u>22</u>	-	20	=	<u>2</u>	x \$ 18.00 = \$ <u>36.00</u>
d) Fee for Multiple Claims						\$270.00 = \$ _____

Total Filing Fee \$ 796.00

- ( ) Statement(s) of Status as Small Entity, reducing filing fee in half to \$ \_\_\_\_\_
- ( ) A check in the amount of \$\_\_\_\_\_ to cover the filing fee is enclosed.
- ( ) Charge \$\_\_\_\_\_ to Deposit Account No. \_\_\_\_\_
- ( ) Other \_\_\_\_\_

Suite 8660 - Sears Tower  
233 South Wacker Drive  
Chicago, Illinois 60606  
(312) 993-0080

GREER, BURNS & CRAIN, LTD.

By: \_\_\_\_\_

Steven P. Fallon

Registration No. 35,132

I hereby certify that this paper is being deposited with the United States Postal Service as Express Mail in an envelope addressed to: BOX PATENT APPLICATION, ASSISTANT COMMISSIONER FOR PATENTS, Washington, D.C. 20231, on this date

04/08/99

Date

Express Mail No. EM045518299US

# MICROFLUIDIC EMBRYO AND/OR OOCYTE HANDLING DEVICE AND METHOD

## FIELD OF THE INVENTION

The present invention generally concerns handling of embryos. The invention also concerns handling of oocytes (prefertilized embryos). Embryo, as used herein, therefore encompasses oocytes as well as fertilized embryos. The invention more specifically concerns microfluidic handling of embryos for culturing, manipulation, and analysis.

## BACKGROUND OF THE INVENTION

Technology assisted reproduction techniques in which embryos are handled independently from their mammalian biological source are growing in importance and frequency of use. Such techniques have great direct benefit to persons unable to have babies through unassisted sexual reproduction. The agricultural industries also increasingly rely upon such assisted reproduction techniques. Embryo manipulation is used in livestock reproduction to control such things as the faster genetic evolution of cattle and permitting the genetic characteristics of a single exceptional cow or bull to be passed on to far greater numbers of offspring than would be possible through unassisted sexual reproduction.

Livestock embryo manipulation is becoming more routine due to the development of gene manipulation, cloning, and *in vitro* fertilization (IVF) techniques. The

1 overall goal of embryo manipulation in livestock is to increase production efficiency,  
2 especially with regard to reproduction, milk production or production of specific milk  
3 components, lean tissue growth with reduced fat content and decreased susceptibility to  
4 specific diseases. Embryo transfer is also used to introduce or rescue valuable germplasm  
5 and propagate rare breeding animals such as endangered exotic species.

6 Expense and relatively low success rates place significant burdens on the use  
7 of these assisted reproduction techniques for humans as well as livestock. In human  
8 reproduction such expense and failure adds emotional as well as economic burdens. In  
9 addition, safeguards against failures often result in unwanted or unmanageable multiple  
10 births, as well as additional stored embryos which require maintenance and additional  
11 difficult decision making at some later point in time. Expense is the primary concern in  
12 livestock reproduction.

13 Failure rates in reproduction techniques as well as testing and other embryo  
14 handling techniques are attributable primarily to the significant handling and manipulation  
15 of embryos in executing these techniques. Animal reproductive technologies have advanced  
16 in recent years, but the physical tools used in animal reproduction have not changed  
17 significantly. Fine-bore glass pipets are still one of the basic tools of the embryologist.  
18 Using standard petri dishes, procedures such as in vitro maturation of eggs (IVM), *in vitro*  
19 fertilization, and embryo culture (EC) require picking up and placing individual eggs and  
20 embryos several times for each procedure.

21 Such handling and movement from one petri dish to another provides  
22 significant potential for damage or contamination. Perhaps more important, though, is the  
23 failure of a stationary embryo in a petri dish to simulate the corresponding natural biological  
24 reproduction condition. Some efforts have been made to move embryos in petri dishes via  
25 agitation of the dish, but this is a haphazard approach. Expense is also created here due to  
26 the relatively large amount of biological medium required for the manual petri dish

1 conventional embryo handling methods. Bovine embryos are individually handled with  
2 pipets and large, expensive manipulators. Large quantities of biological medium including  
3 growth agents for human embryo culturing renders the corresponding *in vitro* procedure even  
4 more expensive. Livestock growth factors, for example, have costs exceeding \$200 per  
5 50 $\mu$ g.

6 Such static culture systems also fail to allow for changing the milieu in the  
7 culture medium as the embryo develops. Current culture systems with flowing medium have  
8 culture chambers as small as 0.2 to 0.5 ml. However, the culture volumes are greater than  
9 needed and medium is replenished too quickly. The endogenous growth factors that enhance  
10 development are diluted out and washed away. The large volumes of medium required  
11 substantially increase costs when expensive growth factors, such as IGF-II (\$200 per 50  $\mu$ g)  
12 are used. In addition, known systems cannot track individual embryos.

13 Thus, there is a need for an improved embryo handling device and method  
14 which addresses problems in known embryo handling techniques. An improved embryo  
15 handling device and method should provide for an improved simulation of natural conditions.  
16 It should also provide a building block upon which larger and/or more powerful and accurate  
17 instruments may be based, such as embryo culturing systems, embryo analysis systems,  
18 embryo storage systems, and similar systems.

## 19 SUMMARY OF THE INVENTION

20 These needs are met or exceeded by the present microfluidic embryo handling  
21 device and method. The invention simulates biological rotating of embryos. An embryo  
22 fluidic channel moves an embryo inserted therein with fluid, and is sized on the same scale  
23 as the particular type of embryo or embryos to be handled. The sizing and fluid  
24 communication produces a simulated biological rotating of embryos. In addition, the fluid  
25 flow with and around the embryo or embryos prevents stagnation, reducing the likelihood

1 of the embryo or embryos developing “bed sores”.

2 The invention also permits the biological medium fluid to be altered gradually,  
3 having significant advantages compared to repeatedly manually transferring an embryo from  
4 one medium to another medium in a pipet or petri dish. Gradual changes avoid the shock  
5 from sudden changes in local environment. The microfluidic system of the invention further  
6 permits the co-culturing of an embryo with other embryos, co-culturing of an embryo or  
7 embryos with cells upstream of the embryo(s), and maintenance of a separate control culture  
8 that shares a common biological medium with a subject embryo(s) thereby ensuring that test  
9 embryos see the same environmental conditions as the subject embryo(s).

#### 10 BRIEF DESCRIPTION OF THE DRAWINGS

11 Other objects, features and advantages of the invention will be apparent to  
12 artisans who read the detailed description and reference the accompanying drawings, of  
13 which:

14 FIG. 1 shows a cross section of a preferred microfluidic embryo handling  
15 device constructed in accordance with the present invention;

16 FIG. 2(a) is a top view showing a preferred narrow microfluidic channel  
17 constriction for embryo positioning;

18 FIG. 2(b) is a cross-sectional view of an alternate preferred shallow  
19 microfluidic channel constriction for embryo positioning;

20 FIG. 3 is a perspective view of a preferred gravity flow driven microfluidic  
21 culturing and testing device constructed in accordance with the present invention;

22 FIG. 4 is a block diagram of an embryo analysis device constructed in accordance  
23 with the present invention;

24 FIGS. 5(a) - 5(c) illustrate preferred embryo microfluidic channel insertion and  
25 removal structures in accordance with the present invention; and

FIGS. 6(a) - 6(b) illustrate a preferred culturing device constructed in accordance with the present invention.

### DETAILED DESCRIPTION OF THE INVENTION

The present invention provides a microfluidic embryo handling device which reduces stress to embryos handled outside their natural biological host. The device and method reproduce simulated biological rotating of an embryo through fluid assisted movement in a channel that encourages embryo slipping and rotating. Rotating, as used herein, may include complete rotation or partial rotation. Partial rotation might also be referred to as a rocking motion.

Referring now to FIG. 1 shown is a cross-section of a microfluidic embryo handling device 10 including a embryo transport network 12 formed at least in part by a generally embryo scale channel 14. An embryo 16 in the channel 14 will move with fluid flow in the channel 14, while the close dimensions of the channel cause the embryo 14 to move with a simulated biological rotating motion. In biological hosts, developing embryos in their initial stages of development move toward the uterus to which they will attach with a rotating and slipping motion. The microfluidic channel 14 produces a simulation of such motion.

Sizing of a channel is important to establish the biological rotating. Height is the critical dimension, and it has been found that heights up to about three times the diameter of an embryo induce the rotating. This ratio may be determined to vary somewhat because fluid flow also plays a role, but the three to one maximum ratio has been found to produce the rotating. It will be appreciated that the channel width is less important. The width may be selected arbitrarily. Thus, if embryos are to be kept in single order, then the width would be less than twice the embryo diameter. If more embryos are desired, larger width channels may be used.

1            Networks of the channels 14 provide a means to culture embryos, as well as  
2 to move and place embryos to desired locations. During its initial stages of development, the  
3 size of most mammalian embryos remain generally constant during the first few days after  
4 fertilization. Thus, the size of the channels 14 provide no impediment to culturing an embryo  
5 therein. Advantageously, the embryo 16 may be kept moving and/or may have a continuous  
6 or pulsed fluid flow passed around it to avoid potential detrimental biological effects on the  
7 embryo 16.

8            A preferred exemplary construction of a device 10 including a channel is also  
9 illustrated in FIG. 1. The microfluidic channel 14 may be formed by any suitable  
10 micromachining technique into a suitable material, such as a silicon wafer 18. The material  
11 chosen must be capable of being sterilized and should not pose a biological threat to  
12 embryos. The channel(s) 14 of the device are sealed through a cover 20. Forming the cover  
13 of glass or other transparent material allows convenient visual monitoring of embryos in  
14 channel(s) 14. A bonding agent 22 bonds the cover 20 to the wafer 18. Additionally, the  
15 material of the cover could be formulated to shield harmful radiation from the embryo(s) in  
16 channel(s) 14.

17            Unlike other cells that tend to float in a fluid medium, the relatively large and  
18 heavy embryos sink to the bottom of the microfluidic channels 14. Typical mammalian  
19 preimplantation embryos of interest are 90 to 180  $\mu\text{m}$  diameter spheres. In each embryo, a  
20 membrane surrounds each cell (blastomere) and the zona pellucida, a glycoprotein membrane  
21 or shell, surrounds the entire cell mass. The cells divide several times during the first few  
22 days after fertilization, the volume of the embryo remains constant and an egg may be  
23 fertilized and cultured to a blastocyst in the same device constructed based upon the  
24 principles of the invention. The blastocyst is the final stage before an embryo implants in  
25 the uterus.

Also important to production of such a device and similar devices is the ability to handle individual embryos, or small numbers of embryos. Positioning embryos to given locations, moving to alternate locations, and maintaining constant or changing biological conditions around the embryo(s) are abilities provided by basic principles of the present invention, and permit the construction of fertilization, culturing, testing, and other devices which rely on some or all of those abilities. For continuous movement of an embryo through a culture period of time, long channels may be created, or a loop may be formed. Alternately, a parking of an embryo may occur at a culturing station like those shown in FIGS. 6(a) and 6(b). A compartment or channel of limited size may also be used to roll an embryo back and forth therein by changing fluid flow, as will be further discussed with respect to FIGS. 6(a) and 6(b).

Accurate positioning of individual embryos is provided by the invention through the use of constrictions, preferred examples of which are shown in FIGS. 2a and 2b. Fig. 2(a) is a top view of a cross section of a narrow constriction 24 formed in a microfluidic channel 14. There are many reasons such an accurate positioning may be desirable in an embryo handling device 10. Analysis instruments built into the device may require an embryo to be precisely positioned at electrodes, a photodetector, the focal point of a microscope, or other similar sensing device. Transporting an embryo to the constriction 24 permits such required positioning without resort to feedback systems. An embryo 16 is freed from the constriction 24 simply by reversing the flow of biological fluid medium 30. Even when held at the constriction, an embryo 16 experiences a flow of biological fluid medium around it since fluid 30 will flow past it and through the constriction 24. This is advantageous since an embryo in stagnant fluid has an increased potential to develop "bed sores", a suspected but yet unproven explanation for low success rates in embryo handling technology.



1 Sidewall portions 28a, 28b of the microfluidic channel 14 constrict it at a  
2 desired location to prevent passage of an embryo 16 therethrough. The constriction 24 does  
3 not completely close the microfluidic channel 14 so that fluid biological medium 30 may  
4 pass an embryo 16 positioned at the constriction 24. FIG. 2(b) shows a side cross-section of  
5 an alternate shallow constriction 26 where the fluid biological medium 30 is similarly able  
6 to pass when an embryo 16 is positioned at the constriction. Other shapes of constriction are  
7 also possible. Generally, any shape which prevents passage of an embryo 16 while  
8 simultaneously allowing fluid flow through the constriction, e.g., asymmetric shapes and  
9 comb-like fibers, is acceptable to position embryos in a device 10 according to the invention.  
10 It is preferred that the constriction be sized such that positioning of an embryo prevents the  
11 embryo from passing without an increased pressure from the fluid pressure used in a device  
12 10 to move embryos. Constriction length should also be kept small enough to avoid fluid  
13 control problems since the constriction portion of a microfluidic channel will have much  
14 higher fluidic resistance per unit length than unrestricted portions of the microfluidic  
15 channels 14.

16 A culture and test device 31 including a constriction like that shown in FIG.  
17 2(a) for positioning an embryo is illustrated in FIG. 3. The device 31 has fluid flow in a  
18 network 32 of microfluidic channels 14 driven by gravity based upon levels of fluid 30 in a  
19 plurality of fluid reservoirs 34. Any suitable means for driving fluid 30 is contemplated as  
20 being compatible with the general principles of the invention, e.g. pumping, but the gravity  
21 method illustrated in FIG. 3 is preferred for its simplicity and efficiency. Directions of flows  
22 are controlled simply by levels of fluid in reservoirs 34. Thus, for example, an embryo 16  
23 held at a constriction 24 for culturing or examination by a suitable instrument is positioned  
24 by first setting fluid levels to cause its travel from inlet port 36 to constriction 24, and is  
25 released when fluid flow is reversed through the construction 24. Removal of the embryo  
26 16 is accomplished by causing fluid flow to move it to exit port 38.

1 During movement through the microfluidic channels 14 of the network 32, the  
2 embryo(s) roll and slip to simulate natural movement of embryos toward a uterus in a  
3 mammalian host, as discussed above. This desirable manner of moving may be aided by a  
4 suitable surfactant such as BSA (bovine serum albumin). The surfactant will help to promote  
5 some slippage of the embryo as it rolls.

6 FIG. 3 also illustrates an additional advantage of the invention, in the provision  
7 of a parallel additional microfluidic handling and culturing device 31a. The additional device  
8 31a has a structure similar to that of device 31, but may have fewer or even a single  
9 microfluidic channel. Ideally, the structure is the same. The important feature of the device  
10 31a is that it shares a common fluid source with inlet port 36 and outlet port 38 of primary  
11 device. Embryo(s) handled in the device 31a are isolated biologically from embryo(s) in  
12 primary device 31, but experience the same biological conditions through sharing the same  
13 fluidic source, pressure and/or the same biological medium condition. In an exemplary use,  
14 the additional device 31a therefore might form an important control culture in which  
15 development or lack of development of test embryo(s) could confirm suitability or  
16 unsuitability of conditions created in the primary device 31.

17 FIG.4 is a block diagram of an embryo analysis device. In the FIG. 4 device  
18 a network 32 of microfluidic channels 14 moves embryos to one or more analysis stations  
19 40a, 40b or 40c. Embryos are positioned at a given analysis station through constrictions like  
20 those described above. The analysis stations may include any instrument capable of  
21 obtaining information concerning an embryo, with the constriction being formed to position  
22 embryos at the proper sensing point for the particular instrument used in an analysis station.  
23 Embryos are moved out of the device through one or more exit ports 38a, 38b, which might  
24 alternately lead to a culturing station in the form of a parking area for an embryo, an  
25 additional length of microfluidic channel 14, or a microfluidic channel loop for continuous  
26 movement of an embryo during culturing.

Inlet and outlet ports used in devices of the invention may comprise any conventional manner or structure for embryo insertion or removal. However, additional preferred structures for insertion and removal are shown in FIGS. 5(a) - 5(c). In FIG. 5(a), a well 42 which is in fluid communication with a microfluidic channel 14 is used. Fluid in the well 42 preferably also comprises a gravity feed which helps drive microfluidic flow in the channel 14. An embryo 16 is placed in the well 42 and moves into the channel 14 with biological medium, or simply sinks unaided into the channel 14 if no flow condition is created. A second similar well 42 may be used to remove an embryo using a pipet 44 or similar device, which might also be used for insertion. In FIG. 5(b), a hanging drop 46 at the end of a channel 14 is used for insertion and removal. The hanging drop 46 is held by surface tension. After embryo insertion, fluid may be added at that point, or the embryo may be sucked in by fluid flow in the device. Alternately, the device may be inclined to promote embryo movement away from the hanging drop 46. In FIG. 5(c), a funnel shaped hole 48 in direct communication with channel 14 is used for insertion and removal. The funnel shape aids positioning of a pipet 44 or similar device. Surface tension at a small diameter hole 48 will prevent fluid from leaking out, but the pressure in channel 14 must not exceed the point that would defeat surface tension and cause fluid to leak out. Inserted embryos will sink into the channel 14, while removal may be accomplished by drawing fluid from hole 48 when an embryo approaches. Of course, any of the FIG. 5 techniques may be combined with each other or conventional techniques for insertion and removal in a given handling device. In addition, the wells 42 or holes 48 may be covered by a removable cover or flap as protection against contamination and/or evaporation.

Referring now to FIGS. 6(a) and 6(b), an embryo culturing device 50 according to the present invention is shown. Fluid medium flow in the culture device 50 is in either direction between a medium inlet 52 and a medium outlet 54. The device includes a number of traps or compartments 56. As best seen in FIG. 6(b), the traps 56 comprise deep regions

1 separated by shallow regions 58. Fluid flow between inlet 52 and outlet 54 is over shallow  
2 regions and through deep regions to move embryos back and forth within the deep region  
3 compartments 56. Embryos are inserted and removed through access holes 60, which may  
4 be formed by any of the preferred methods in FIGS. 5(a) through 5(c). In the device 50,  
5 artisans will thus appreciate that embryos may be moved back and forth within compartments  
6 56 to simulate biological rotating, may experience the same medium conditions as other  
7 embryos within the culture, and may be easily removed and inserted. Though FIGS. 6(a) and  
8 6(b) show a top loading embodiment for placing embryos within the compartment, the device  
9 will also work in a bottom loading arrangement, essentially inverted from that shown in  
10 FIGS. 6(a) and 6(b). In such a bottom loading arrangement, the embryos will still be held  
11 in the deep portions but cannot pass the shallow portions. An alternate embodiment might  
12 comprise a gap in place of shallow constructions where embryos cannot pass through the  
13 gaps but fluid flow may occur therebetween and the depth of the gaps may be the same as  
14 those of the embryo holding compartments.

15         Prototype devices like that shown in FIG. 3 have been produced and tested.  
16 Typical prototypes are described here for the sake of completeness. Artisans will appreciate  
17 that the manner of fabricating the prototypes may be accomplished by any other convention  
18 microfabrication techniques. Artisans will also appreciate that production device  
19 manufacturing may differ significantly, and that specific numerical dimensions and  
20 conditions of the prototype devices do not limit the invention in the breadth described above.

21         In typical prototype channels, a pressure gradient of 1 Pa/mm causes the  
22 medium to flow on the order of  $10^{-10}$  m<sup>3</sup>/s (100 nl/s), with an average speed of 1 to 2 mm/s.  
23 Under these flow conditions the embryos roll along the bottoms of the channels; traveling  
24 at speeds ranging from 1/3 to 1/2 that of the fluid that would otherwise be in the same region  
25 of the channel. By manipulating the pressure at the wells connected to the ends of the  
26 channels, the embryos can be transported to (and retained at) specific locations including

1 culture compartments and retrieval wells. Embryos fill a considerable portion of the channel,  
2 thereby greatly altering the flow of medium. The flow of medium through the channels is  
3 laminar.

4 Networks of prototype microfluidic channels have been fabricated in a device  
5 like that shown in FIG. 3 by etching trenches in 3-inch <100> silicon wafers, and then  
6 bonding glass covers to form channels. Typical channel networks contain several branch  
7 microfluidic channels that intersect near the center of the device. The branches, which range  
8 from 1.5 to 2.5 cm in length, are 160 to 200  $\mu\text{m}$  deep and 250 to 350  $\mu\text{m}$  wide at the top. A  
9 first step in producing prototype devices involves patterning silicon nitride (SiN) coatings  
10 on using conventional photolithography techniques. The microfluidic channels are  
11 anisotropically etched with a potassium hydroxide (KOH) solution. Access holes in the glass  
12 covers are drilled, either conventionally using carbide tipped bits or ultrasonically. Glass  
13 covers are bonded to the wafers using UV curable epoxy (NOA 61, Norland Products, Inc,  
14 New Brunswick, NJ) or Pyrex 7740 covers are anodically bonded to the wafers using 500V  
15 in a 450°C environment. The nitride coatings are removed using buffered oxide etchant  
16 (BOE) before anodic bonding. Glass wells are bonded to the glass cover at the end of each  
17 branch of the channel network with either an epoxy (Quick Stick 5 Minute Epoxy or 5 Hour  
18 Set Epoxy Glue; both from GC Electronics, Rockford, IL) or a silicone adhesive (RTV 108  
19 and RTV 118 from General Electric Co., Waterford, NY, or Sylgard® Brand 184, Dow  
20 Corning Corp., Midland, MI).

21 In the prototype devices, constrictions like those in both of FIGS. 2(a)  
22 ("narrow") and 2(b) ("shallow") have also been fabricated and tested. Channels with  
23 "narrow" constrictions, as shown in FIG. 2(a), can be fabricated using a single mask and  
24 etching operation. Channels with the "shallow" constrictions, as shown in FIG. 2(b), require  
25 two masks and two etching operations.

1 All the component materials of the prototype devices except the five minute  
2 epoxy were tested for embryo biocompatibility. In applying the present invention, artisans  
3 will appreciate that alternate materials may be used from those selected for the prototype  
4 devices, but biocompatibility must always be established through prior data and/or testing.  
5 Although many materials are known to be compatible with or toxic to certain cells, little  
6 work has been done to investigate the compatibility of materials used in micro fabrication  
7 with embryos. The materials selected may also vary depending upon the type of mammal  
8 from which the specific embryos to be handled are taken.

9 In prototype testing, two-cell mouse embryos (B6SJL/F2) were randomly  
10 assigned to and cultured on the substrata, in medium M16 (Sigma, St. Louis, MO) with  
11 bovine serum albumin (BSA; 4 mg/ml; Sigma), covered with mineral oil (Sigma). All  
12 embryos were cultured at 37°C in a 5% CO<sub>2</sub> in air atmosphere for 96 h. Developmental rates  
13 of embryos were examined every 24 h. The percentage of embryos that reached the  
14 blastocyst stage for each material was compared with the percentage from the control group.  
15 Mouse embryos that reach the blastocyst stage, the latest possible stage before embryo  
16 transfer, are probably not developmentally hindered. While the absence of negative effects  
17 is not guaranteed unless the embryos are also transferred to recipient mice and monitored  
18 until the offspring are born, tests are commonly concluded at the blastocyst stage for  
19 practical and economic reasons. Most of the materials tested proved to be compatible with  
20 the mouse embryos, including silicon wafers, SiN coatings, NOA 61, and RTV 118. Some  
21 materials, such as the 5-minute epoxy, have not been tested since it is only used in conceptual  
22 devices to demonstrate mechanical and fluidic principals of the invention, and would likely  
23 not be used in production devices.

24 Tests were run to examine several aspects of the prototype devices. Different  
25 tests required devices with different channel configurations. In all the tests, a halogen bulb  
26 via optical fibers illuminated the channel, which was viewed under a stereomicroscope. A

1 graduated cylinder and a stopwatch were used to determine flow rates. Since the fluid is  
2 incompressible, the average fluid velocity in any section of channel is just the flow rate  
3 divided by the cross-sectional area.

4           Measurements of the rate of travel of the embryo for a given flow rate occurred  
5 in a simple straight channel, 29 mm long, 162  $\mu\text{m}$  deep, and 160 - 380 (bottom - top)  $\mu\text{m}$   
6 wide. The pressure gradient was varied and the speed of the embryo was measured for each  
7 setting. The channels were filled with phosphate buffered saline (PBS), with and without  
8 BSA. Flasks of the medium were connected to the channel. By adjusting the heights of the  
9 flasks, using micrometer head translation stages, the pressure difference was finely tuned to  
10 within 0.05 Pa. The flasks were connected to each other by tubing between the tests to zero  
11 the pressure head. The microfabricated prototype devices were cleaned in a hydrogen  
12 peroxide/ammonium hydroxide/deionized water solution and new pipet tips were adhered  
13 with epoxy before the tests were conducted. All the tests using PBS without BSA were  
14 conducted before those with BSA. Once the channels were filled with medium the mouse  
15 embryos were placed in the inlet well, at the channel entrance.

16           Tests were run to observe the influence of channel size and shape on the  
17 transport of embryos. For these tests, a device was fabricated with one long, circuitous  
18 channel with 11 sections each at one of four depths: 140, 164, 194, and 210  $\mu\text{m}$ . At each  
19 depth the channel has 2 or 3 different widths. Widths, measured at the surface of the wafer,  
20 range from 275 to 480  $\mu\text{m}$ . In the narrowest segments, the embryos were geometrically  
21 constrained to travel on a V-groove while in the other regions along a flat-bottomed channel.  
22 The speed of travel and rotating characteristics were observed and compared for different  
23 segments.

24           Observations of embryos at constrictions occurred in several devices, with both  
25 narrow and shallow type constrictions. Embryos were actually directed to specific  
26 constrictions. Altering the height of the medium in each well, by adding or subtracting fluid,

1 tailored the pressure gradients in each branch of the channel network. Pressure heads were  
2 adjusted by a 1 to 8 mm (10 to 80 Pa).

3 Just as embryos placed in medium sink to the bottom of the container, embryos  
4 placed in microfluidic channels settle to the bottom. In all the tests, when the medium  
5 flowed, the embryos rolled and slid along the bottom of the channel in the direction of flow.  
6 Often they also remained in contact with one of the side walls of the channel. In initial tests  
7 without any surfactant in the medium (phosphate buffered saline) the embryos appeared to  
8 roll without slipping along the bottoms of the channels. Embryos slid or rolled with slip  
9 along the bottoms in later tests when the medium contained BSA (4 mg/ml).

10 Tests revealed that the rate of travel of an embryo in a channel depends upon  
11 the velocity of the medium. Sometimes they stick to the bottom of the channel when the  
12 velocity of the fluid around them is below  $50 \mu\text{m/s}$ . For both media, PBS and PBS/BSA, a  
13 pressure gradient of  $0.16 \text{ Pa/mm}$  drives the flow through the channel at an average velocity  
14 of approximately  $380 \mu\text{m/s}$ . The embryos rolled at  $187 - 250 \mu\text{m/s}$ , 49 to 66% of  $380 \mu\text{m/s}$ .  
15 As the medium flows more quickly, the embryos roll faster, slipping as they roll. The actual  
16 speed of travel and the tendency to stick varies from one embryo to the next. One embryo has  
17 been observed to travel 25% quicker than another at the same time in the same channel, in  
18 almost the same path line. In the observed range,  $150$  to  $1000 \mu\text{m/s}$ , the velocity is linear  
19 with pressure gradient.

20 Results from testing the effects of channel size and shape match *a priori*  
21 predictions. For a given flow rate, the average fluid velocity and embryo speed is greater in  
22 a channel with smaller cross-sectional area. In contrast, for a given pressure gradient, the  
23 average fluid velocity and embryo speed is greater in a channel with larger cross-sectional  
24 area. In both cases, embryos travel slower on V-grooves than on flat-bottomed channels.  
25 Embryos are also more likely to become wedged and stuck in a V-groove than on a flat-  
26 bottomed channel.



Fluid under electroosmotic flow also caused embryos to roll through channels. An embryo rolled along the channel bottom at approximately  $10\ \mu\text{m/s}$  due to the pressure driven trickle flow. Switching on the voltage caused the mouse embryo to roll along the channel bottom  $20\ \mu\text{m/s}$  faster, at approximately  $30\ \mu\text{m/s}$ , toward the well with the negative electrode. With the voltage polarity reversed, the embryo rolled at approximately  $10\ \mu\text{m/s}$  in the reverse direction. No surfactant, such as BSA was used so there was little or no slipping. Electric assistance was determined to be undesirable due to its heating of the medium.

Computational fluid dynamics modeling using Fluent/UNS 4.2 (Fluent, Inc., Lebanon, NH) and 2-dimensional finite element analysis of prototype microfluidic channels with constant cross-section using Quickfield (Tera Analysis, Inc., Tarzana, CA) verified the observed flow rates and flow patterns. The embryo was modeled as a rigid sphere. Recall that the embryo does not appear to deform under typical conditions. To analyze the laminar flow, 1 or 2 mm sections of channel were meshed into 10,000 to 30,000 tetragonal elements. Once verified, computer modeling was used to determine flow velocity profiles, design constrictions with lower pressure drops, to observe forces on embryos retained at constrictions, and to analyze electrically driven flows in similar channels. However, analysis incorporating adhesion of the embryo to the channel walls and distortion of the embryo would be significantly more complex and was not attempted.

As discussed above, in the straight channel tests of embryo velocity, the medium had an average velocity of  $380\ \mu\text{m/s}$  under a pressure gradient of  $0.16\ \text{Pa/mm}$ . Finite element analyses determined the centerline velocity to be  $815\ \mu\text{m/s}$  under these conditions. When traveling in the channel, the embryo was tangent to the bottom and one wall. Consider a  $100\ \mu\text{m}$  diameter circle tangent to the bottom and one side of the channel. The average velocity of the fluid traveling through this circle when the embryo is not present is  $480\ \mu\text{m/s}$ . However, the embryos rolled at only  $187 - 250\ \mu\text{m/s}$ , 39 - 52% as quickly, in

1 both PBS and PBS/BSA media. The velocity profile encourages the embryo to roll forward  
2 and along the wall, which confirms visual observations. In sum, embryos roll at  $\frac{1}{3}$  to  $\frac{1}{2}$  the  
3 speed at which fluid would flow in the same region of the cross section.

4 The constrictions greatly increase fluidic resistance in the channels. Standard  
5 analytical formulas can help approximate the resistance, but the cross-sectional shapes of the  
6 constrictions vary with position. Three-dimensional models of the constrictions were  
7 analyzed before masks were designed and wafers were etched. The information gained from  
8 the finite element analyses led to optimally-sized constrictions. The shallow constrictions,  
9 sized individually for the geometry of the device, balance the need for minimal flow  
10 resistance and robust fabrication. Typical constrictions have a minimal depth of 20  $\mu\text{m}$ .

11 Studies of the placement of the embryos at the traps reveal lateral forces on the  
12 order of  $10^{-8}$  to  $10^{-7}$  N force the embryo to the side and part way up the ramp at the entrance  
13 to the shallow constriction.

14 The tests revealed several interesting characteristics of microfluidic transport,  
15 such as variations in velocity between embryos and the tendency to roll along the bottoms  
16 of the channels, often tangent to a side wall. However, the testing did reveal several other  
17 issues. Electrical control of fluid flow was investigated initially, but the high voltages harm  
18 the embryos in several ways. Even with the embryos in sections of channel away from the  
19 electric fields, the applied energy heats up the medium (Joule heating) beyond physiological  
20 temperatures and the electrolysis products alter the pH. Note that an embryo requires about  
21 0.029 Osmol, i.e., a relatively high conductivity. Also, EOF is degraded in channels with  
22 surfactant, but the embryos survive better in medium with a surfactant, such as BSA.

23 Microfluidic transport free of electrical assistance offered through gravity fed  
24 devices like that in FIG. 3, or through pumped fluid pressure devices, offers an important  
25 advantage. The medium can be easily altered with time to meet the changing requirements  
26 of the developing embryos. Gradually changing the composition of the medium avoids

1 inducing stresses upon the embryo from the abrupt environmental changes that often  
2 accompany transfer from one petri dish to a second dish with a different medium. The  
3 microfluidic handling of embryos by the invention is not physically harsher than transfer  
4 with pipets and definitely less damaging than many techniques in conventional practice  
5 including some which pierce the outer membrane.

6 It is anticipated that control of fluid flow, and therefore embryo positioning,  
7 in handling devices like that shown in FIG. 3 will be handled through programmed control  
8 instruments for largely automated devices. Alarms and warnings may be incorporated based  
9 upon sensed conditions within an embryo handling device of the invention. In similar  
10 fashion, monitoring of embryos with conventional instruments applied to a handling device  
11 of the present invention. Artisans will generally recognize that the microfluidic embryo  
12 handling device thus forms a basic building block upon which many useful devices may be  
13 based, and that such devices will incorporate the essence of the present invention.

14 While various embodiments of the present invention have been shown and  
15 described, it should be understood that other modifications, substitutions and alternatives are  
16 apparent to one of ordinary skill in the art. Such modifications, substitutions and alternatives  
17 can be made without departing from the spirit and scope of the invention, which should be  
18 determined from the appended claims.

19 Various features of the invention are set forth in the appended claims.

WHAT IS CLAIMED IS:

1           1.     A microfluidic embryo handling device comprising:  
2           an embryo transport network having a biological medium for movement of  
3           embryos inserted therein, said transport network including an approximate embryo scaled  
4           embryo fluidic channel to facilitate simulated biological rotating of individual embryos  
5           moving within said fluidic channel.

1           2.     The microfluidic embryo handling device of claim 1, wherein said  
2           transport network is formed in a wafer and said embryo fluidic channel comprises a  
3           microchannel in said wafer.

1           3.     The microfluidic embryo handling device of claim 1, further  
2           comprising:

3           a biological medium source for introducing said biological medium into said  
4           embryo transport network in a continuous flow manner; and

5           a control test embryo network fed said biological medium from said biological  
6           medium source, said control test embryo network being biologically isolated from said  
7           embryo transport network.

1           4.     The microfluidic embryo handling device of claim 1, further  
2           comprising:

3           a gravity controlled biological medium source for introducing said biological  
4           medium into said embryo transport network in a continuous flow manner.

1           5.     The microfluidic embryo handling device of claim 1, further comprising  
2 a formation in a path defined by said communication channel for holding an embryo at a  
3 desired location while maintaining flow of said biological medium past an embryo held at  
4 said desired location.

1           6.     The microfluidic embryo handling device of claim 5, wherein said  
2 formation comprises a constriction.

1           7.     The microfluidic embryo handling device of claim 6, further  
2 comprising:

3                 a biological medium source for maintaining flow of said biological medium  
4 and for reversing flow of said biological medium to free an embryo held at said desired  
5 location.

1           8.     The microfluidic embryo handling device of claim 1, wherein said  
2 fluidic channel has a flat bottom.

1           9.     The microfluidic embryo handling device of claim 1, wherein said  
2 fluidic channel has a V-shaped bottom.

1           10.    The microfluidic embryo handling device of claim 1, wherein said  
2 simulated biological rotating includes rotating and slipping.

1           11. The microfluidic embryo handling device of claim 1, further  
2 comprising:

3           a controlled biological medium source for introducing said biological medium  
4 into said embryo transport network in a continuous flow manner unassisted by electrical  
5 stimulus.

1           12. The microfluidic embryo handling device of claim 1, wherein movement  
2 of embryos in said embryo transport network is unassisted by electrical stimulus.

1           13. The microfluidic embryo handling device of claim 1, wherein said  
2 transport network is sealed from surrounding environment and said device further comprises  
3 an embryo entrance to said transport network and an embryo exit from said transport  
4 network.

1           14. The microfluidic embryo handling device of claim 13, wherein said  
2 embryo entrance comprises a hole penetrating a sealing member which seals said transport  
3 network, said hole maintaining separation between said biological medium and surrounding  
4 environment through surface tension.

1           15. The microfluidic embryo handling device of claim 14, further  
2 comprising a removable cover to seal said hole.

1           16. The microfluidic embryo handling device of claim 14, wherein said hole  
2 is funnel shaped.

1                   17.    The microfluidic embryo handling device of claim 14, wherein said hole  
2 is located in a midstream portion of said transport network.

1                   18.    The microfluidic embryo handling device of claim 13, wherein said  
2 embryo entrance comprises a well in fluid communication with said transport network.

1                   19.    The microfluidic embryo handling device of claim 13, wherein said  
2 embryo entrance comprises a hanging drop.

1                   20.    The microfluidic embryo handling device of claim 1, wherein said  
2 fluidic channel comprises an embryo compartment defining a culturing station for an embryo  
3 and said device further comprises smaller than embryo diameter fluid flow channels for  
4 moving fluid through said embryo compartment.

1                   21.    A microfluidic embryo handling device, comprising:  
2 a fluid path for moving an embryo inserted therein by fluid flow unassisted by  
3 electrical stimulus;  
4 surfaces defining at least a part of said fluid path and spaced to promote  
5 rotating of said embryo as it moves in said fluid path.

1                   22.    A method of handling embryos comprising steps of:  
2 moving an embryo through exclusive use of fluid flow;  
3 rotating said embryo as said step of moving is executed.

1 MICROFLUIDIC EMBRYO AND/OR  
2 OOCYTE HANDLING DEVICE AND METHOD




3 ABSTRACT


4 A microfluidic embryo handling device and method in which biological  
5 rotating of embryos is simulated. Fluid flow is used to move and position embryos without  
6 assistance of electrical stimulus or other means which may produced undesired heating of  
7 biological medium used as the fluid for transporting and position. Continuous or pulsed flow  
8 is maintained around an embryo or embryos in the device. The device provides an excellent  
9 simulation of biological conditions and may be used for culturing, sorting, testing,  
10 evaluating, fertilizing and other similar typical handling operations. An embryo may be  
11 parked at a desired location to carry out such a typical operation, while the microfluidic  
12 handling device maintains fluid flow around the embryo.

13  
14  
15  
16  
17  
18  
19  
20  
21  
22  
23  
24  
25  
26  
27  
28  
29  
30  
31  
32  
33  
34  
35  
36  
37  
38  
39  
40  
41  
42  
43  
44  
45  
46  
47  
48  
49  
50  
51  
52  
53  
54  
55  
56  
57  
58  
59  
60  
61  
62  
63  
64  
65  
66  
67  
68  
69  
70  
71  
72  
73  
74  
75  
76  
77  
78  
79  
80  
81  
82  
83  
84  
85  
86  
87  
88  
89  
90  
91  
92  
93  
94  
95  
96  
97  
98  
99  
100  
101  
102  
103  
104  
105  
106  
107  
108  
109  
110  
111  
112  
113  
114  
115  
116  
117  
118  
119  
120  
121  
122  
123  
124  
125  
126  
127  
128  
129  
130  
131  
132  
133  
134  
135  
136  
137  
138  
139  
140  
141  
142  
143  
144  
145  
146  
147  
148  
149  
150  
151  
152  
153  
154  
155  
156  
157  
158  
159  
160  
161  
162  
163  
164  
165  
166  
167  
168  
169  
170  
171  
172  
173  
174  
175  
176  
177  
178  
179  
180  
181  
182  
183  
184  
185  
186  
187  
188  
189  
190  
191  
192  
193  
194  
195  
196  
197  
198  
199  
200  
201  
202  
203  
204  
205  
206  
207  
208  
209  
210  
211  
212  
213  
214  
215  
216  
217  
218  
219  
220  
221  
222  
223  
224  
225  
226  
227  
228  
229  
230  
231  
232  
233  
234  
235  
236  
237  
238  
239  
240  
241  
242  
243  
244  
245  
246  
247  
248  
249  
250  
251  
252  
253  
254  
255  
256  
257  
258  
259  
260  
261  
262  
263  
264  
265  
266  
267  
268  
269  
270  
271  
272  
273  
274  
275  
276  
277  
278  
279  
280  
281  
282  
283  
284  
285  
286  
287  
288  
289  
290  
291  
292  
293  
294  
295  
296  
297  
298  
299  
300  
301  
302  
303  
304  
305  
306  
307  
308  
309  
310  
311  
312  
313  
314  
315  
316  
317  
318  
319  
320  
321  
322  
323  
324  
325  
326  
327  
328  
329  
330  
331  
332  
333  
334  
335  
336  
337  
338  
339  
340  
341  
342  
343  
344  
345  
346  
347  
348  
349  
350  
351  
352  
353  
354  
355  
356  
357  
358  
359  
360  
361  
362  
363  
364  
365  
366  
367  
368  
369  
370  
371  
372  
373  
374  
375  
376  
377  
378  
379  
380  
381  
382  
383  
384  
385  
386  
387  
388  
389  
390  
391  
392  
393  
394  
395  
396  
397  
398  
399  
400  
401  
402  
403  
404  
405  
406  
407  
408  
409  
410  
411  
412  
413  
414  
415  
416  
417  
418  
419  
420  
421  
422  
423  
424  
425  
426  
427  
428  
429  
430  
431  
432  
433  
434  
435  
436  
437  
438  
439  
440  
441  
442  
443  
444  
445  
446  
447  
448  
449  
450  
451  
452  
453  
454  
455  
456  
457  
458  
459  
460  
461  
462  
463  
464  
465  
466  
467  
468  
469  
470  
471  
472  
473  
474  
475  
476  
477  
478  
479  
480  
481  
482  
483  
484  
485  
486  
487  
488  
489  
490  
491  
492  
493  
494  
495  
496  
497  
498  
499  
500  
501  
502  
503  
504  
505  
506  
507  
508  
509  
510  
511  
512  
513  
514  
515  
516  
517  
518  
519  
520  
521  
522  
523  
524  
525  
526  
527  
528  
529  
530  
531  
532  
533  
534  
535  
536  
537  
538  
539  
540  
541  
542  
543  
544  
545  
546  
547  
548  
549  
550  
551  
552  
553  
554  
555  
556  
557  
558  
559  
560  
561  
562  
563  
564  
565  
566  
567  
568  
569  
570  
571  
572  
573  
574  
575  
576  
577  
578  
579  
580  
581  
582  
583  
584  
585  
586  
587  
588  
589  
590  
591  
592  
593  
594  
595  
596  
597  
598  
599  
600  
601  
602  
603  
604  
605  
606  
607  
608  
609  
610  
611  
612  
613  
614  
615  
616  
617  
618  
619  
620  
621  
622  
623  
624  
625  
626  
627  
628  
629  
630  
631  
632  
633  
634  
635  
636  
637  
638  
639  
640  
641  
642  
643  
644  
645  
646  
647  
648  
649  
650  
651  
652  
653  
654  
655  
656  
657  
658  
659  
660  
661  
662  
663  
664  
665  
666  
667  
668  
669  
670  
671  
672  
673  
674  
675  
676  
677  
678  
679  
680  
681  
682  
683  
684  
685  
686  
687  
688  
689  
690  
691  
692  
693  
694  
695  
696  
697  
698  
699  
700  
701  
702  
703  
704  
705  
706  
707  
708  
709  
710  
711  
712  
713  
714  
715  
716  
717  
718  
719  
720  
721  
722  
723  
724  
725  
726  
727  
728  
729  
730  
731  
732  
733  
734  
735  
736  
737  
738  
739  
740  
741  
742  
743  
744  
745  
746  
747  
748  
749  
750  
751  
752  
753  
754  
755  
756  
757  
758  
759  
760  
761  
762  
763  
764  
765  
766  
767  
768  
769  
770  
771  
772  
773  
774  
775  
776  
777  
778  
779  
780  
781  
782  
783  
784  
785  
786  
787  
788  
789  
790  
791  
792  
793  
794  
795  
796  
797  
798  
799  
800  
801  
802  
803  
804  
805  
806  
807  
808  
809  
810  
811  
812  
813  
814  
815  
816  
817  
818  
819  
820  
821  
822  
823  
824  
825  
826  
827  
828  
829  
830  
831  
832  
833  
834  
835  
836  
837  
838  
839  
840  
841  
842  
843  
844  
845  
846  
847  
848  
849  
850  
851  
852  
853  
854  
855  
856  
857  
858  
859  
860  
861  
862  
863  
864  
865  
866  
867  
868  
869  
870  
871  
872  
873  
874  
875  
876  
877  
878  
879  
880  
881  
882  
883  
884  
885  
886  
887  
888  
889  
890  
891  
892  
893  
894  
895  
896  
897  
898  
899  
900  
901  
902  
903  
904  
905  
906  
907  
908  
909  
910  
911  
912  
913  
914  
915  
916  
917  
918  
919  
920  
921  
922  
923  
924  
925  
926  
927  
928  
929  
930  
931  
932  
933  
934  
935  
936  
937  
938  
939  
940  
941  
942  
943  
944  
945  
946  
947  
948  
949  
950  
951  
952  
953  
954  
955  
956  
957  
958  
959  
960  
961  
962  
963  
964  
965  
966  
967  
968  
969  
970  
971  
972  
973  
974  
975  
976  
977  
978  
979  
980  
981  
982  
983  
984  
985  
986  
987  
988  
989  
990  
991  
992  
993  
994  
995  
996  
997  
998  
999  
1000

F:\DATA\WP60\1201\62820\62820 APP







660410 2ET66260




FIG 5 (a)




FIG 5 (b)




FIG 5 (c)






FIG. 6(a)

 Shallow Region  
 Deep Region




FIG. 6(b)

Section A-A

## **DECLARATION AND POWER OF ATTORNEY**

As a below named inventor, I hereby declare:

That my residence, post office address and citizenship are as stated below next to my name.

That I verily believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural inventors are named below) of the subject matter which is claimed and for which a patent is sought on the invention entitled:

### **MICROFLUIDIC EMBRYO AND/OR OOCTE HANDLING DEVICE AND METHOD**

the specification of which (check one)

( X ) is attached hereto.

( ) was filed on \_\_\_\_\_ as  
Application Serial No. \_\_\_\_\_  
and was amended on \_\_\_\_\_  
(if applicable)

That I have reviewed and understand the contents of the above-identified specification, including the claims, as amended by any amendment referred to above.

That I acknowledge the duty to disclose information known to be material to patentability of this application in accordance with Title 37, Code of Federal Regulations, §1.56(a).

That I hereby claim foreign priority benefits under Title 35, United States Code, §119 of any foreign application(s) for patent or inventor's certificate listed below and have also identified below any foreign application for patent or inventor's certificate on this invention having a filing date before that of the application on which priority is claimed:

#### **Prior Foreign Application(s)**

#### **Priority Claimed**

_____ (Number)	_____ (Country)	_____ (Day/Month/Year Filed)	<input type="checkbox"/> Yes	<input type="checkbox"/> No
_____ (Number)	_____ (Country)	_____ (Day/Month/Year Filed)	<input type="checkbox"/> Yes	<input type="checkbox"/> No
_____ (Number)	_____ (Country)	_____ (Day/Month/Year Filed)	<input type="checkbox"/> Yes	<input type="checkbox"/> No

That I hereby claim the benefit under Title 35, United States Code, §120 of any United States application(s) listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States application in the manner provided by the first paragraph of Title 35, United States Code, §112, I acknowledge the duty to disclose material information as defined in Title 37, Code of Federal Regulations, §1.56(a) which occurred between the filing date of the prior application and the national or PCT international filing date of this application:

#### **United States Application(s)**

_____ (Application Serial No.)	_____ (Filing Date)	_____ (Status)-(Patented, pending, abandoned)
_____ (Application Serial No.)	_____ (Filing Date)	_____ (Status)-(Patented, pending, abandoned)
_____ (Application Serial No.)	_____ (Filing Date)	_____ (Status)-(Patented, pending, abandoned)

That all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issuing thereon.

I hereby appoint the following attorneys and agents, with full power of substitution and revocation, to prosecute this application and to transact all business in the United States Patent and Trademark Office connected therewith and request that all correspondence and telephone calls in respect to this application be directed to GREER, BURNS & CRAIN, LTD., Suite 8660 - Sears Tower, 233 South Wacker Drive, Chicago, Illinois 60606, Telephone No. (312) 993-0080:

<u>Attorney</u>	<u>Registration No.</u>
Roger D. Greer	26,174
Patrick G. Burns	29,367
Lawrence J. Crain	31,497
Steven P. Fallon	35,132
James K. Folker	37,538
B. Joe Kim	41,895
Jonathan D. Feuchtwang	41,017
Joel H. Bootzin	42,343

Full name of sole or one joint inventor: David J. Beebe

Inventor's signature: \_\_\_\_\_

Date: \_\_\_\_\_

Residence and Post Office Address: 602 Wesley Avenue

Savoy, Illinois 61874

Citizenship: United States

Full name of additional joint inventor, if any: Ian K. Glasgow

Inventor's signature: \_\_\_\_\_

Date: \_\_\_\_\_

Residence and Post Office Address: 3910 Fern Court

Madison, Wisconsin 53711-1615

Citizenship: United States

Address for Correspondence: Steven P. Fallon  
GREER, BURNS & CRAIN, LTD.  
Suite 8660 - Sears Tower  
233 South Wacker Drive  
Chicago, Illinois 60606

Full name of additional  
joint inventor, if any:

Matthew B. Wheeler

Inventor's signature:

Date:

Residence and Post Office Address:

246 County Road 1400E

Tolono, Illinois

Citizenship:

United States

Full name of additional  
joint inventor, if any:

Inventor's signature:

Date:

Residence and Post Office Address:

Citizenship:

Full name of additional  
joint inventor, if any:

Inventor's signature:

Date:

Residence and Post Office Address:

Citizenship:

Address for Correspondence:

Steven P. Fallon  
GREER, BURNS & CRAIN, LTD.  
Suite 8660 - Sears Tower  
233 South Wacker Drive  
Chicago, Illinois 60606  
(312) 993-0080